

## Uni Mata



**Uni Mata**, soft glass wool available in rolls. Unfaced insulation applied where high insulation properties are required.

### Application:

Thermal and acoustic insulation suitable in:

- timber sloping roofs in between rafters
- timber and steel frame walls
- suspended timber ground floors
- partition and suspended ceiling.

### Characteristics:

Max. usage temperature: 200°C

- easy to cut, handle and minimizes dust during installation
- air and vapour permeable

### Uni Mata - technical specification

Product	Thickness [mm]	Width [mm]	Lenght [mm]	R <sub>D</sub> [m <sup>2</sup> K/W]	Quantity [m <sup>2</sup> /pack]	Qty im MPS [m <sup>2</sup> /pallet]
Uni Mata	50	1200	2x8000	1,25	19,20	460,80
Uni Mata	80	1200	2x5500	2,05	13,20	316,80
Uni Mata	100	1200	8000	2,55	9,60	230,40
Uni Mata	120	1200	7000	3,05	8,40	201,60
Uni Mata	140	1200	6250	3,55	7,50	180,00
Uni Mata	150	1200	5750	3,85	6,90	165,60
Uni Mata	180	1200	4750	4,60	5,70	136,80
Uni Mata	200	1200	4250	5,10	5,10	122,40